

# MATERIAL SAFETY DATA SHEET

## DAUBERT CHEMICAL COMPANY

4700 SOUTH CENTRAL AVENUE  
CHICAGO, ILLINOIS 60638  
TELEPHONE: (708) 496-7350  
FAX: (708) 496-7367

EMERGENCY CONTACT:  
CHEMTREC (800) 424-9300

## HMIS HAZARD RATING

|                     |   |
|---------------------|---|
| HEALTH              | 1 |
| FIRE                | 0 |
| REACTIVITY          | 0 |
| PERSONAL PROTECTION | D |

Date of Review:

Date of Preparation: May 8, 2002

Revised:

By: J. Kuksuk

## SECTION 1: PRODUCT IDENTIFICATION

Product Name: **NON-SKID 1903 Black**  
Chemical Family: Water, Additive Blend  
Material Usage: Coating Compound

EMERGENCY OVERVIEW: Water-based product. Alkaline liquid; may be irritating to eyes and skin. Refer to Section 3 for health effects and to Section 5 for fire hazard data.

## SECTION 2: HAZARDOUS INGREDIENTS

| Component  | Wt%   | Recommended Exposure Limits (TWA)   |
|--|-------|---|
| <sup>(1)</sup> Silica, Crystalline Quartz<br>CAS #14808-60-7 | 40-50 | OSHA PEL: 0.1 mg/m <sup>3</sup> (respirable dust)<br>ACGIH TLV: 0.1 mg/m <sup>3</sup> (respirable dust) |
| <sup>(1)</sup> Mica<br>CAS #12001-26-2                       | 5-7   | OSHA PEL: 20 mppcf ( <sup>(1)</sup> nuisance dust)<br>ACGIH TLV: 3 mg/m <sup>3</sup>                    |
| <sup>(1)</sup> Carbon Black<br>CAS #1333-86-4                | 1-3   | OSHA:PEL: 3.5 mg/m <sup>3</sup> ( <sup>(2)</sup> nuisance dust)<br>ACGIH TLV: None Established          |
| Ammonium Hydroxide<br>CAS #1336-21-6                         | <0.5  | OSHA PEL: 35 ppm<br>ACGIH TLV: 25 ppm   |

<sup>(1)</sup> See Section 3

<sup>(2)</sup> This component poses a hazard only if a dust is formed, i.e., by sawing, sanding, drilling, etc

### SECTION 3: HEALTH HAZARD INFORMATION

Primary Routes of Entry: Inhalation, skin absorption

Acute Effects: May cause severe eye irritation and reversible skin irritation. Prolonged skin exposure may cause dermatitis or oil acne. Breathing mists may cause pulmonary irritation or dizziness. Excessive inhalation may produce dizziness, nausea, headache, and incoordination.

Chronic Effects: Not determined

Effects of Overexposure: Not determined

Carcinogenicity:

Silica Crystalline Quartz (CAS #14808-60-7): (Mica may also contain more than 0.1% of Silica.) IARC Monographs on the evaluations of the Carcinogenic Risk of Chemicals to Humans (Volume 42, 1987) concludes that there is "limited evidence" of the carcinogenicity of crystalline silica to humans. IARC classification 2A.

Carbon black has been classified by IRAC as a Category 2B (known animal carcinogen, possible human carcinogen) material. This was based on the results of rat inhalation studies of carbon black, despite the lack of parallel evidence on humans or other animal species.

Pre-Existing Medical Conditions Aggravated by Exposure: Exposure may aggravate pre-existing respiratory or skin problems.

### SECTION 4: FIRST AID PROCEDURES

Inhalation: Move victim to fresh air and call emergency medical care. If not breathing, give artificial respiration; if breathing is difficult, give oxygen.

Eyes: In case of contact with material, immediately flush eyes with running water for at least 15 minutes. Seek immediate medical attention.

Skin: Wash skin with soap and water. Remove and isolate contaminated clothing and shoes at the site.

Ingestion: DO NOT INDUCE VOMITING. Consult a physician. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs.

### SECTION 5: FIRE AND EXPLOSION HAZARD DATA

Flash Point: : Not Applicable (Water Based Fluid)

Explosive Limits: LEL = Not determined UEL = Not determined

EXTINGUISHING MEDIA:

Small Fires: Dry chemical, CO<sub>2</sub>, water spray, or regular foam.

Large Fires: Water spray, fog, or regular foam. Move container from fire area if you can do it without risk. Apply cooling water to sides of containers that are exposed to flames until well after fire is out. Stay away from ends of tanks.

Special Firefighting Protection/Emergency Action: Fire may produce irritating or poisonous gases. Positive pressure self-contained breathing apparatus (SCBA) and structural firefighters' protective clothing will provide limited protection.

Unusual Fire/Explosion Hazards: None

Products of Combustion: Carbon monoxide, carbon dioxide, oxides of sulfur, miscellaneous hydrocarbons.

### SECTION 6: SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

Steps to be Taken in case Material is Released or Spilled: Shut off ignition sources; no flares, smoking or flames in hazard area. Stop leak if you can do it without risk.

Small Spills: Take up with sand or other noncombustible absorbent material and place into containers for later disposal.

Large Spills: Dike far ahead of liquid spill for later disposal.

## SECTION 7: SAFE HANDLING INFORMATION

Precautions To Be Taken In Handling/Storage: Store in cool, well-ventilated area. Keep away from flames, sparks or hot surfaces. Never use a torch to cut or weld on or near container. Empty containers can contain explosive vapors.

Other Precautions: Never wear contaminated clothing. Launder or dry clean before wearing. Discard oil-soaked shoes. Wash thoroughly with soap and water (waterless hand cleaner may be helpful in removing residues) after use and before smoking or eating. Avoid excessive skin contact.

## SECTION 8: EXPOSURE CONTROLS

Respiratory Protection: NIOSH-approved respirator for organic vapor and mist to control exposure where ventilation is inadequate.

Ventilation: General and local exhaust.

Personal Protective Equipment:

Protective Gloves: Impervious gloves (Viton, PVOH, etc.)

Eye Protection: Safety glasses with sideshields or chemical goggles.

Other Protective Clothing or Equipment: If splashing is anticipated, wear rubber apron and boots or other protective equipment to minimize contact.

## SECTION 9: REACTIVITY HAZARD DATA

Stability: Stable

Incompatibility: Strong acids, oxidizing agents.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, oxides of sulfur, miscellaneous hydrocarbons.

Hazardous Polymerization: Will not occur.

## SECTION 10: PHYSICAL AND CHEMICAL PROPERTIES

|   |                 |
|---|-----------------|
| Color:                                  | Black           |
| Appearance:                             | Paste           |
| Odor:                                   | Mild            |
| Boiling Point (initial): °F             | Not Determined. |
| Evaporation Rate (n-Butyl Acetate = 1): | < 1             |
| Vapor Pressure (mmHg @ 20°C):           | Not Determined  |
| Vapor Density (air = 1):                | > 1             |
| Solubility in Water:                    | Negligible      |
| Specific Gravity:                       | 1.49            |
| pH:                                     | Not Applicable  |
| Percent Volatile by Volume:             | 48              |

**SECTION 11: DISPOSAL CONSIDERATIONS**

Waste Disposal Methods: Dispose of in accordance with state, local and federal regulations. Materials may become a hazardous waste through use. If permitted, incineration may be practiced. Consider recycling solvent

**SECTION 12: REGULATORY INFORMATION**

Volatile Organic Content: (Calculated Values)

VOC per gallon: 0.15 lbs/gal

EPA Hazardous Waste Number(s) (40 CFR Part 261): Not applicable

EPA Hazard Category (40 CFR Part 370): DELAYED (CHRONIC)

**SARA TITLE III:**

This product contains the following TOXIC CHEMICALS subject to the Reporting Requirements of Sec. 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986, and of 40 CFR Part 372:

| Chemical         | CAS No.   | Wt%  |
|------------------|-----------|------|
| Cobalt Compounds | 7440-48-4 | <0.1 |

This product contains the following EXTREMELY HAZARDOUS SUBSTANCE(S) subject to Emergency Planning Requirements under Sec. 301-303 (40 CFR Parts 300 and 355) and Emergency Release Notification Requirements under Sec. 304:

| Chemical | CAS No | Wt% | RQ/TPQ Lbs |
|----------|--------|-----|------------|
| None     |        |     |            |

This product contains the following (CERCLA LIST) HAZARDOUS SUBSTANCE(S) subject to Emergency Release Notification Requirements under Sec 304 (40 CFR Part 302):

| Chemical           | CAS No.   | Wt%  | Final RQ Lbs |
|--------------------|-----------|------|--------------|
| Ammonium Hydroxide | 1336-21-6 | <0.5 | 1000         |

**CALIFORNIA PROPOSITION 65:**

This product may contain trace quantities of the following chemicals that are identified by the State of California under the Safe Drinking Water and Toxic Reinforcement Act of 1986 ("Proposition 65") as either a carcinogenic or reproductive hazard:

| Chemical                   | CAS No.    | Estimated Concentration % |
|----------------------------|------------|---------------------------|
| Silica, Crystalline Quartz | 14808-60-7 | 40-45                     |
| Mica                       | 12001-26-2 | 3-5                       |

All Mica products listed contain:  
Crystalline Silica >0.1 %

|              |           |     |
|--------------|-----------|-----|
| Carbon Black | 1333-86-4 | 1-3 |
|--------------|-----------|-----|

\*\*\*\*\*

Although the information contained herein is believed to be reliable, it is furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.