



PRODUCT INFORMATION SHEET C-35 Rubberized Undercoating

Cyclo Industries, Inc
902 S. US Highway 1 • Jupiter, FL 33477 • 561-775-9600

Rubberized Undercoating



- Professional Looking Textured Finish
- Fights Rust & Soundproofs
- Paintable
- Quick Drying
- Blocks Out Salt & Water
- Restores Protection

Directions: **SHAKE WELL** before using until agitator ball moves freely in can. Shake occasionally during use. For best results, use at room temperature. 1. Hold can 10 to 12 inches from a clean, dry surface. 2. Apply an even coat. To avoid rapid buildup of material on surface, keep moving can over surface while spraying. 3. In case of overspray on painted surface, immediately remove with hydrocarbon solvent such as mineral spirits. NOTE: Do not spray on catalytic converters, mufflers, or exhaust pipes. IMPORTANT: Valve should be cleaned after use by turning can upside down for two to three seconds.

Part C-35

Fill: 16 oz / Aerosol

Per Case: 12

UPC: 0 89269 00035 8

Carton UPC: 1 00 89269 00035 5

Shelf Life From Date of Manufacturer: 10+ years

DISCLAIMER: Cyclo Industries, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. Cyclo Industries, Inc. makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, Inc. will not be responsible for damages resulting from use of or reliance upon this information.