CITGO[®] SUPERGARD[®] Marine Plus 2-Cycle Engine Oil



OVERVIEW

- A licensed NMMA® TC-W3® oil that effectively combats wear, scuffing, and deposit build-up, and enhances lubricity to provide longer engine life.
 - Formulated for naturally carbureted outboard engines.

FEATURES & BENEFITS



- High film strength for improved lubricity provides increased engine efficiency, excellent scuffing
 protection of rings and cylinders, reduced bearing wear, and cleaner, better-running engines
 producing less smoke.
- Reduces carbon and deposit build-up on engine parts.
- Helps prevent piston ring sticking.
- Guaranteed to protect OEM engine warranties.

APPLICATIONS



- Recommended for all water-cooled or liquid-cooled 2-cycle engines requiring an NMMA TC-W3, TC-WII[®], or TC-W[®] type oil.
- Can be used in many air-cooled 2-cycle engine applications requiring API Service Category TC.
- Recommended for both direct injected and pre-mix systems.
- Provides protection for gasoline-fueled 2-cycle engines when used at the primary dilution recommended by the original equipment manufacturer.
- Refer to equipment owner's manual for proper lubricant recommendation.

Customer Service Line 1-800-331-4068 LubesCS@CITGO.com Product Answer Line 1-800-248-4684 lubeshelp@CITGO.com

Online at www.CITGOLubes.com

Manufactured in USA

PROPERTIES



Typical Properties for CITGO SUPERGARD Marine Plus 2-Cycle Engine Oil:

Material Code	621602001
Gravity, ASTM D4052, °API	31.5
Density, lb/gal at 60°F	7.23
Flash Point, PMCC, ASTM D93, °F (°C)	178 (81)(1)
Flash Point, COC, ASTM D92, °F (°C)	197 (92)
Viscosity ASTM D445	
cSt at 40°C	32.0
cSt at 100°C	5.9
Viscosity ASTM D2161	
SUS at 100°F	163
SUS at 210°F	46
Viscosity Index, ASTM D2270	130
Pour Point ASTM D97, °F (°C)	-38 (-39)
Appearance, Color	Blue/Green
Sulfated Ash, ASTM D874, %	<0.004
Total Base Number, ASTM D2896, mgKOH/g	8.6

(1) Combustible liquid

CITGO and SUPERGARD are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.

CITGO Petroleum Corporation Houston, Texas Customer Service Line 1-800-331-4068 LubesCS@CITGO.com Product Answer Line 1-800-248-4684 lubeshelp@CITGO.com

Online at www.CITGOLubes.com

Manufactured in USA

C 10007