



DESCRIPTION:

PEAK® READY USE® Antifreeze + Coolant is a conventional (green), ethylene glycol based antifreeze for older automotive and light duty diesel applications. PEAK READY USE Antifreeze + Coolant provides protection from freezing, overheating, rust and corrosion when used as recommended.

BENEFITS:

- Compatible with All Conventional (Green) Antifreeze
- For use in: Ford + Chrysler 2000 + earlier, GM 1995 + earlier, All makes all models, 1989 + earlier
- Provides Year-Round Protection Against Damaging Rust and Corrosion
- Prediluted Ready Use formula for topping off

Properties

Properties	Typical Values	ASTM Test Method
Specific Gravity 60/60°F	1.070-1.080	D-1122
Freezing Point	-34°F(-37°C) Max.	D-1177
Boiling Point	265°F (130°C) Min.	D-1120
pH	10.0-11.0	D-1287
Reserve Alkalinity	5.0-7.0	D-1121
Ash, Wt %	2.5 Max.	D-1119
Silicon, ppm	125 Max.	
Chloride, ppm	25 Max.	D-3634
Auto Finish	No Effect	D-1882
Color	Green	

Protection Chart (°F)

*Using a 15 lb. pressure cap

Concentration	50%
Boiling Point*	265
Freezing Point	-34

*At sea level atmospheric pressure with 15lb. pressure cap. The boiling point decreases about 2°F per 1,000 feet of altitude and increases about 2.5°F per pound developed in the system.



Part Number	RUAB53	Cases Per Pallet	36
Gallon UPC	0-74804-00225-6	Pallets/Cases per Truck	20/720
Case UPC	0-74804-10225-3	Units per Truck	4,320
Case SCC-14	1-00-74804-00225-3	Truckload Weight*	42,760lbs.
Pack/Unit Case	6/1 Gallon (3.78 Liters)	Pallet Size	48"L x 40"W x 53 ³ / ₄ "H
Weight/Cube	57 lbs./1.37 cu. ft.	Pallet Weight (inc. A/F & pallet)	2,138 lbs.
Case Dimensions	15.8"L X 12.6"W X 12.25"H	Cases/Rows High	9/4

(*) Includes Pallet Wt.: 20 @ 50 lbs. ea. = 1,000 lbs. Product Liability Information/Material Safety Data available upon request.



Distributed by Old World Industries, LLC Northbrook, IL 60062
p 800.323.5440 www.peakauto.com
 ©2015 PEAK and the PEAK Mountain Graphic are Registered Trademarks of Old World Industries, LLC.
 Long Life is a registered trademark of Warren Distribution, Inc.

RUN TRUE™