

# SAFETY DATA SHEET

## 1. Identification

**Product identifier** Gumout® Carburetor Cleaner

**Other means of identification**

**Synonyms** 29216

**Recommended use** Not available.

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufacturer**

**Company name** ITW Permatex Canada  
**Address** 35 Brownridge Road, Unit 1  
Halton Hills, ON L7G 0C6  
Canada

**Telephone** 1-905-693-8900

**e-mail** Not available.

**Emergency phone number** 1-877-504-9352

**Supplier** See above.

## 2. Hazard identification

<b>Physical hazards</b>	Flammable aerosols	Category 1
	Gases under pressure	Liquefied gas
<b>Health hazards</b>	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Carcinogenicity	Category 2
	Specific target organ toxicity following single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity following single exposure	Category 3 narcotic effects
	Specific target organ toxicity following repeated exposure	Category 2
<b>Environmental hazards</b>	Not classified.	

**Label elements**



**Signal word** Danger

**Hazard statement** Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.  
Causes serious eye irritation.  
Causes skin irritation.  
Suspected of causing cancer.  
May cause damage to organs through prolonged or repeated exposure.  
May cause drowsiness or dizziness.  
May cause respiratory irritation.

**Precautionary statement**

**Prevention** Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.  
Do not breathe mist or vapour.  
Use only outdoors or in a well-ventilated area.  
Wash thoroughly after handling.  
Wear protective gloves/protective clothing/eye protection/face protection.

<b>Response</b>	IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Specific treatment (see information on this label). IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF INHALED: remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell. IF exposed or concerned: Get medical advice/attention.
<b>Storage</b>	Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Other hazards</b>	None known.
<b>Supplemental information</b>	None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Xylene		1330-20-7	40
Acetone		67-64-1	20
Benzene, ethyl-		100-41-4	6.67
2-Pentanone, 4-hydroxy-4-methyl-		123-42-2	4.67

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First-aid measures

<b>Inhalation</b>	IF INHALED: remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell.
<b>Skin contact</b>	IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Specific treatment (see information on this label).
<b>Eye contact</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Ingestion</b>	IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Do NOT induce vomiting.
<b>Most important symptoms/effects, acute and delayed</b>	Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Causes serious eye irritation. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Symptoms may be delayed.
<b>General information</b>	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
<b>Hazardous combustion products</b>	May include and are not limited to: Oxides of carbon.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up.
<b>Specific methods</b>	Move containers from fire area if you can do so without risk. Use standard firefighting procedures and consider the hazards of other involved materials.

**General fire hazards**

Extremely flammable aerosol. Contents under pressure. Pressurised container may explode when exposed to heat or flame.

## 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not breathe mist or vapour. Emergency personnel need self-contained breathing equipment. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up**

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. Prevent entry into waterways, sewer, basements or confined areas.

**Environmental precautions**

Do not discharge into lakes, streams, ponds or public waters.

## 7. Handling and storage

**Precautions for safe handling**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Pressurised container: Do not pierce or burn, even after use.  
 Avoid contact with eyes, skin, and clothing.  
 Wear appropriate personal protective equipment.  
 Do not breathe mist or vapour.  
 Use only in well-ventilated areas.  
 Pregnant or breastfeeding women must not handle this product.  
 Avoid prolonged exposure.  
 Observe good industrial hygiene practices.  
 Wash thoroughly after handling.  
 When using do not eat or drink.

**Conditions for safe storage, including any incompatibilities**

Keep away from heat, sparks and open flame.  
 Store in a well-ventilated place.  
 Store away from incompatible materials (see Section 10 of the SDS).  
 Keep out of reach of children.  
 Store locked up.

## 8. Exposure controls/Personal protection

**Occupational exposure limits****US. ACGIH Threshold Limit Values**

Components	Type	Value
2-Pentanone, 4-hydroxy-4-methyl- (CAS 123-42-2)	TWA	50 ppm
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Benzene, ethyl- (CAS 100-41-4)	TWA	20 ppm
	STEL	150 ppm
Xylene (CAS 1330-20-7)	TWA	100 ppm

**Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

Components	Type	Value
2-Pentanone, 4-hydroxy-4-methyl- (CAS 123-42-2)	TWA	238 mg/m <sup>3</sup>
	STEL	50 ppm
Acetone (CAS 67-64-1)	STEL	1800 mg/m <sup>3</sup>
	TWA	750 ppm
		1200 mg/m <sup>3</sup>
Benzene, ethyl- (CAS 100-41-4)	STEL	500 ppm
	STEL	543 mg/m <sup>3</sup>

**Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

Components	Type	Value
		125 ppm
	TWA	434 mg/m3
		100 ppm
Xylene (CAS 1330-20-7)	STEL	651 mg/m3
		150 ppm
	TWA	434 mg/m3
		100 ppm

**Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)**

Components	Type	Value
2-Pentanone, 4-hydroxy-4-methyl- (CAS 123-42-2)	TWA	50 ppm
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Benzene, ethyl- (CAS 100-41-4)	TWA	20 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

**Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)**

Components	Type	Value
2-Pentanone, 4-hydroxy-4-methyl- (CAS 123-42-2)	TWA	50 ppm
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Benzene, ethyl- (CAS 100-41-4)	TWA	20 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

**Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)**

Components	Type	Value
2-Pentanone, 4-hydroxy-4-methyl- (CAS 123-42-2)	TWA	50 ppm
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
Benzene, ethyl- (CAS 100-41-4)	TWA	20 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

**Canada. Quebec OELs. (Ministry of Labour - Regulation Respecting the Quality of the Work Environment)**

Components	Type	Value
2-Pentanone, 4-hydroxy-4-methyl- (CAS 123-42-2)	TWA	238 mg/m3
		50 ppm
Acetone (CAS 67-64-1)	STEL	2380 mg/m3
		1000 ppm
	TWA	1190 mg/m3
		500 ppm
Benzene, ethyl- (CAS 100-41-4)	STEL	543 mg/m3
		125 ppm
	TWA	434 mg/m3

Canada. Quebec OELs. (Ministry of Labour - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value
Xylene (CAS 1330-20-7)	STEL	100 ppm
		651 mg/m3
	TWA	150 ppm
		434 mg/m3
		100 ppm

**Biological limit values**

**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling time
Acetone (CAS 67-64-1)	25 mg/L	Acetone	Urine	*
Benzene, ethyl- (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Appropriate engineering controls** Ensure adequate ventilation.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection**

**Hand protection** Wear appropriate chemical resistant gloves. Confirm with a reputable supplier first.

**Other** As required by employer code.

**Respiratory protection** Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

**Thermal hazards** Not applicable.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke.

**9. Physical and chemical properties**

<b>Appearance</b>	Aerosol
<b>Physical state</b>	Liquid.
<b>Form</b>	Liquefied gas.
<b>Colour</b>	Not available.
<b>Odour</b>	Solvent
<b>Odour threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	139 - 168 °C (282.2 - 334.4 °F)
<b>Flash point</b>	Not available.
<b>Evaporation rate</b>	> 1 (Butyl acetate = 1)
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Explosive limit - lower (%)</b>	1.1 %
<b>Explosive limit - upper (%)</b>	12.8 %
<b>Vapour pressure</b>	45 - 55 psig @ 20°C
<b>Vapour density</b>	Heavier than air
<b>Relative density</b>	Not available.

<b>Solubility(ies)</b>	
<b>Solubility (Water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	465 - 527 °C (869 - 980.6 °F)
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Explosive properties</b>	Not explosive.
<b>Oxidising properties</b>	Not oxidising.
<b>Specific gravity</b>	0.8 - 0.84

---

### 10. Stability and reactivity

---

<b>Reactivity</b>	May react with incompatible materials.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerisation does not occur.
<b>Conditions to avoid</b>	Heat. Do not mix with other chemicals.
<b>Incompatible materials</b>	Strong oxidising agents.
<b>Hazardous decomposition products</b>	May include and are not limited to: Oxides of carbon.

---

### 11. Toxicological information

---

#### Information on likely routes of exposure

<b>Inhalation</b>	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache.
<b>Skin contact</b>	Causes skin irritation.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. May cause stomach distress, nausea or vomiting.

**Symptoms related to the physical, chemical and toxicological characteristics**      May cause drowsiness and dizziness. Headache. Nausea, vomiting.  
 Causes serious eye irritation.  
 Skin irritation. May cause redness and pain.

#### Information on toxicological effects

**Acute toxicity**      Narcotic effects.

Components	Species	Test results
2-Pentanone, 4-hydroxy-4-methyl- (CAS 123-42-2)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 1875 mg/kg 13500 mg/kg 14.5 ml/kg
<i>Inhalation</i>		
LC50	Not available	
<i>Oral</i>		
LD50	Rat	3002 mg/kg
Acetone (CAS 67-64-1)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	15800 mg/kg 20 ml/kg
<i>Inhalation</i>		
LC50	Mouse	44000 mg/m <sup>3</sup> /4h
	Rat	76 mg/L, 4 Hours 50.1 mg/L, 8 Hours 39 mg/l/4h

Components	Species	Test results
<i>Oral</i> LD50	Human	2857 mg/kg
	Mouse	3000 mg/kg
	Rabbit	5340 mg/kg
	Rat	5800 mg/kg
Benzene, ethyl- (CAS 100-41-4)		
<b>Acute</b>		
<i>Dermal</i> LD50	Rabbit	15380 mg/kg
<i>Inhalation</i> LC50	Rat	4000 ppm, 4 Hours
<i>Oral</i> LD50	Rat	5460 mg/kg 3500 mg/kg
Xylene (CAS 1330-20-7)		
<b>Acute</b>		
<i>Dermal</i> LD50	Rabbit	>= 1700 mg/kg
<i>Inhalation</i> LC50	Mouse	3907 ppm, 6 Hours
	Rat	6350 ppm, 4 Hours 29.1 mg/L, 4 Hours 27.6 mg/L, 4 Hours 21.7 mg/L, 4 Hours
<i>Oral</i> LD50	Mouse	5251 ml/kg 1590 mg/kg
	Rat	3523 - 8600 mg/kg
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Exposure minutes</b>	Not available.	
<b>Erythema value</b>	Not available.	
<b>Oedema value</b>	Not available.	
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.	
<b>Corneal opacity value</b>	Not available.	
<b>Iris lesion value</b>	Not available.	
<b>Conjunctival reddening value</b>	Not available.	
<b>Conjunctival oedema value</b>	Not available.	
<b>Recover days</b>	Not available.	
<b>Respiratory or skin sensitisation</b>		
<b>Canada - Alberta OELs: Irritant</b>		
2-Pentanone, 4-hydroxy-4-methyl- (CAS 123-42-2)	Irritant	
<b>Respiratory sensitisation</b>	Not a respiratory sensitizer.	
<b>Skin sensitisation</b>	This product is not expected to cause skin sensitisation.	
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Carcinogenicity</b>	See below.	
<b>ACGIH Carcinogens</b>		
Acetone (CAS 67-64-1)	A4 Not classifiable as a human carcinogen.	
Benzene, ethyl- (CAS 100-41-4)	A3 Confirmed animal carcinogen with unknown relevance to humans.	
Xylene (CAS 1330-20-7)	A4 Not classifiable as a human carcinogen.	

**Canada - Manitoba OELs: carcinogenicity**

ACETONE (CAS 67-64-1)

Not classifiable as a human carcinogen.

ETHYL BENZENE (CAS 100-41-4)

Confirmed animal carcinogen with unknown relevance to humans.

XYLENE (O, M AND P ISOMERS) (CAS 1330-20-7)

Not classifiable as a human carcinogen.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

Benzene, ethyl- (CAS 100-41-4)

Volume 77 - 2B Possibly carcinogenic to humans.

Xylene (CAS 1330-20-7)

Volume 47, Volume 71 - 3 Not classifiable as to carcinogenicity to humans.

<b>Reproductive toxicity</b>	Not classified.
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness and dizziness. May cause respiratory irritation.
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	Not classified.
<b>Chronic effects</b>	May cause damage to organs through prolonged or repeated exposure.
<b>Further information</b>	Not available.

---

**12. Ecological information**

---

**Ecotoxicity** See below**Ecotoxicological data**

<b>Components</b>		<b>Species</b>	<b>Test results</b>
2-Pentanone, 4-hydroxy-4-methyl- (CAS 123-42-2)			
<b>Aquatic</b>			
Fish	LC50	Bluegill ( <i>Lepomis macrochirus</i> )	420 mg/L, 96 hours
Acetone (CAS 67-64-1)			
Crustacea	EC50	Daphnia	13999 mg/L, 48 Hours
<b>Aquatic</b>			
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> )	10294 - 17704 mg/L, 48 hours
Fish	LC50	Rainbow trout, donaldson trout ( <i>Oncorhynchus mykiss</i> )	4740 - 6330 mg/L, 96 hours
Benzene, ethyl- (CAS 100-41-4)			
Algae	IC50	Algae	4.6 mg/L, 72 Hours
Crustacea	EC50	Daphnia	2.1 mg/L, 48 Hours
<b>Aquatic</b>			
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> )	1.37 - 4.4 mg/L, 48 hours
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> )	7.5 - 11 mg/L, 96 hours
Xylene (CAS 1330-20-7)			
<b>Aquatic</b>			
Fish	LC50	Bluegill ( <i>Lepomis macrochirus</i> )	7.711 - 9.591 mg/L, 96 hours
<b>Persistence and degradability</b>	No data is available on the degradability of this product.		
<b>Bioaccumulative potential</b>			
<b>Mobility in soil</b>	No data available.		
<b>Mobility in general</b>	Not available.		
<b>Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

---

**13. Disposal considerations**

---

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

## 14. Transport information

**General** Canada: TDG Proof of Classification: In accordance with Part 2.2.1 (SOR/2014-152) of the Transportation of Dangerous Goods Regulations, we certify that the classification of this product is correct as of the SDS date of issue. If applicable, the technical name and the classification of the product will appear below.

### Transportation of Dangerous Goods (TDG - Canada)

**Basic shipping requirements:**

**UN number** UN1950  
**Proper shipping name** AEROSOLS, flammable  
**Hazard class** 2.1  
**Special provisions** 80, 107

TDG



## 15. Regulatory information

**Canadian federal regulations** This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

**Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number**

Xylene (CAS 1330-20-7) 1 TONNES

**Export Control List (CEPA 1999, Schedule 3)**

Not listed.

**Greenhouse Gases**

Not listed.

**Precursor Control Regulations**

Acetone (CAS 67-64-1) Class B

**WHMIS status** Controlled

**International regulations**

**Inventory status**


Country(s) or region	Inventory Name	On Inventory (Yes/No)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

## 16. Other information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

<b>HEALTH</b>	* 2
<b>FLAMMABILITY</b>	4
<b>PHYSICAL HAZARD</b>	1
<b>PERSONAL PROTECTION</b>	X



**Issue date** 06-April-2017

**Revision date** 06-April-2017

**Version No.** 01

**Other information** For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.

**Disclaimer**

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

**Prepared by**

Dell Tech Laboratories Ltd. Phone: (519) 858-5021