

Perlube 100

Lubricating Oil

Description

Perlube 100 is a light viscosity, highly refined lubricating oil that may be used for a variety of applications where anti-wear or EP properties are not required.

Key Properties

- Low odor gives good operator acceptance
- Clear and light colored
- Chlorine Free
- Non-sulfurized

Typical Specifications:

TEST	RESULT
ASTM, Color	1.0
Viscosity @ 100°F (sus)	95 – 120
Fat	None
Chlorine	None
Sulfur	None
Anti-Wear Additives	None
Flash Point °F, (coc) min	320
Lbs per Gallon	7.5

Applications

- Machine lubrication, hydraulic fluid, circulating oil
- Light duty cutting, grinding, and polishing

Material Compatibility

Perlube 100 is safe to use with all metals including aluminum, brass and copper.

Safe Handling and Storage Instructions

Before handling and using, the Safety Data Sheet (SDS) should be read and understood by all personnel in contact with this product. Indoor storage at temperatures above freezing is recommended.

Disposal

Any disposal of this product should be in compliance with all federal, state and local regulations. Please refer to the Safety Data Sheet (SDS) for instructions regarding proper disposal of this product.

Precautions

KEEP OUT OF THE REACH OF CHILDREN. Please refer to the label and Safety Data Sheet for all warnings, recommendations for safety equipment, and other regulatory information. Copies of the Safety Data Sheet (SDS) can be ordered by calling 800-438-2647.

This information is presented in good faith, but no warranty, expressed or implied is given. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. This is an uncontrolled copy and changes can be made to this document without notice.