

PRODUCT INFORMATION



VALVOLINE™ UNITRAC FLUID

Valvoline Unitrac Fluid is a high performance, multi-purpose all-weather fluid designed for agricultural tractors and off-highway equipment. **Unitrac Fluid** is uniquely formulated to provide excellent anti-wear, oxidation, ferrous rust, copper corrosion, sludge and varnish protection. It is designed to reduce wet brake and PTO chatter. This product is recommended for use in the hydraulic systems, final drives, transmissions, differentials, wet brake systems, PTOs and hydrostatic drives.

Meets or exceeds the following specifications (Where appropriate viscosity grade applies):

John Deere JDM J20C,
New Holland Group(Ford New Holland) – FNHA-2-C-201.00(134D), FNHA-2-C-200.00
Massey Ferguson M1135, M1139, M1141 (Permatran®III), M1143, M1145,
Case Corporation (Case I.H., J.I. Case) – MS-1207 (Hy-Tran® Plus), MS-1210, MS-1209 (Hy-Tran Ultra)
Kubota UDT Hydraulic Fluid, Universal Transdraulic Fluid
White Farm (Oliver) – Q-1826 Hydraulic, Transmission Fluid HTF
Case New Holland MAT 3505, MAT 3525, MAT 3526, ESN M2C86B, ESN M2C86C
Agco(Duetz-Allis) – Power Fluid 821XL
Steiger Hydraulic/Transmission Fluid SEMS 17001
Landini Tractor II Hydraulic Fluid; Hesston Fiat Oilofiat Tutela Multi-F
Sundstrand Hydrostatic Transmission Fluid, Hydraulic Fluids
Allison Type C-4 Fluid
Komatsu AXO 80
API GL-4
Denison Hydraulic Fluid HF-0, HF-2, HF-1 All Pumps, Vickers M-2950-S Mobil Hydraulic & I-286-S Industrial Hydraulics
Clark Lift Truck Transmission Fluid TA12, TA18, HR500, HR600
Volvo VCE 1273.03, WB 101

Meets or exceeds the following older or obsolete specifications (Where appropriate viscosity grade applies):

Caution: *Some of these specifications are no longer deemed active by the original equipment manufacturer. Significant harm to the transmission, hydraulic system, final drive or axles is possible when using this product.*

John Deere JDM J20A, J20B, J14B, & JD 303; Ford New Holland ESN-M2C134-C, ESN-M2C134B, ESN-M2C134A, ESN-M2C86B, ESN-M2C53A, ESN-M2C48-B&C; Massey Ferguson M-1129-A, M-1127-B, M-1127-A, M-1110; Case B-6(HY-TRAN®), MS-1206 (PTF), MS-1205, MS-1204/JIC-185, JIC-144, JIC-143, B-5; White Farm (Oliver) Q-1802(Type 55 Fluid), Q-1766B (Universal HTF), Q-1722 (White MP Tractor Oil), Q-1705 (Universal HTF); Agco (Allis) 257541, 246634; Versatile Hydraulic /Gear Fluid Spec 24M, Spec 23M; Hesston Fiat AF-87; Oliver Q-1802 (Type 55), Allison C-3 Fluid; Caterpillar TO-2

Typical Properties:	Unitrac
KV100 (cSt)	9.4
KV40 (cSt)	58
Viscosity Index	141
Specific Gravity @ 60°F	0.871
Pour Point (°C)	-45
Brookfield Vis @ -35°C, cP	32,000
CCS @ -25°C, cP, max	7,000

Part Numbers:	Unitrac
Bulk	VV8100
Tote	VV810
55 Gallon Drum	VV813
5 Gallon Pail	853217

This information only applies to products manufactured in the following location(s): USA

Effective Date:
1/21/19

Author's Initials:
KD